

WHAT IS CLAIMED IS:

1. A liquid crystal shutter comprising:
a liquid crystal device including a nematic liquid crystal sealed
5 in between a first transparent substrate and a second transparent
substrate on whose inner surfaces are formed respective transparent
electrodes, said liquid crystal device having a twisted angle equal to or
greater than 180° ; and
a pair of polarizing plates between which are sandwiched said
10 first transparent substrate and said second transparent substrate, said
polarizing plates having respective absorption axes which are
substantially orthogonal to each other, said absorption axes of said
polarizing plates being angled within a range of $\pm 40^\circ$ to $\pm 50^\circ$ relative to
15 a direction in which intermediate liquid crystal molecules are orientated,
said direction indicating a direction of orientation of said liquid crystal in
an intermediate portion in a direction of thickness of said liquid crystal
device.
2. A liquid crystal shutter comprising:
20 a liquid crystal device including a nematic liquid crystal sealed
in between a first transparent substrate and a second transparent
substrate on whose inner surfaces are formed respective transparent
electrodes, said liquid crystal device having a twisted angle equal to or
greater than 180° ; and
25 a pair of polarizing plates between which are sandwiched said

0098154-010000

substrate and said
having respec
onal to each oth
within a range o
gence Δn of sa
transparent sub

3

5

10

$\Delta n d$ lies within a range of 600 to 900 nm, said $\Delta n d$ being the product of a birefringence Δn of said nematic liquid crystal and a gap d between said first transparent substrate and said second transparent substrate.

15

4.

20

25

5. A liquid crystal shutter driving method according to claim 4, wherein

a positive or negative driving voltage is applied to said liquid crystal shutter during a partial period within said scan term, said driving voltage being set to 0V during a remaining period, said period during which said driving voltage is set to 0V being varied to perform a gradation display.

10 6. A liquid crystal shutter driving method according to claim 4, wherein

the voltage applied to said liquid crystal shutter in said scan term is varied from 0V to perform a gradation display.

15 7. A liquid crystal shutter driving method according to claim 4, wherein

a single driving term of said liquid crystal shutter is controlled, depending on an operating temperature, so as to be increased at a time of a low temperature but reduced at a time of a high temperature.

20

8. A method of driving a liquid crystal shutter according to claim 1, wherein

a single driving term of said liquid crystal shutter is assigned to a scan term during which all pixels or predetermined pixels of said liquid crystal shutter are rendered opened or half-opened, said scan term being

25

00001654-010000

controlled, depending on an operating temperature, so as to be lengthened at a time of a low temperature but shortened at a time of a high temperature.

- 5 9. A method of driving a liquid crystal shutter according to claim 2, wherein

a single drive term of said liquid crystal shutter is divided into a reset term during which all pixels of said liquid crystal shutter are rendered closed and a scan term during which all the pixels or
10 predetermined pixels are rendered opened or half-opened;

the duration of said scan term being made shorter than a holding time taken for a transmittance of said liquid crystal shutter to start to lower after it has reached its maximum with no driving voltage applied to said liquid crystal shutter.

15

10. A liquid crystal shutter driving method according to claim 9, wherein

a positive or negative driving voltage is applied to said liquid crystal shutter during a partial period within said scan term, said driving
20 voltage being set to 0V during a remaining period, said period during which said driving voltage is set to 0V being varied to perform a gradation display.

11. A liquid crystal shutter driving method according to claim 9,
25 wherein

0000154-010000

the voltage applied to said liquid crystal shutter in said scan term is varied from 0V to perform a gradation display.

12. A liquid crystal shutter driving method according to claim 9,
5 wherein

a single driving term of said liquid crystal shutter is controlled, depending on an operating temperature, so as to be increased at a time of a low temperature but reduced at a time of a high temperature.

- 10 13. A method of driving a liquid crystal shutter according to claim 2, wherein

a single driving term of said liquid crystal shutter is assigned to a scan term during which all pixels or predetermined pixels of said liquid crystal shutter are rendered opened or half-opened, said scan term being
15 controlled, depending on the operating temperature, so as to be lengthened at a time of a low temperature but shortened at a time of a high temperature.

14. A method of driving a liquid crystal shutter according to claim 3,
20 wherein

a single drive term of said liquid crystal shutter is divided into a reset term during which all pixels of said liquid crystal shutter are rendered closed and a scan term during which all the pixels or predetermined pixels are rendered opened or half-opened;

- 25 the duration of said scan term being made shorter than a holding

time taken for a transmittance of said liquid crystal shutter to start to lower after it has reached its maximum with no driving voltage applied to said liquid crystal shutter.

- 5 15. A liquid crystal shutter driving method according to claim 14, wherein

a positive or negative driving voltage is applied to said liquid crystal shutter during a partial period within said scan term, said driving voltage being set to 0V during a remaining period, said period during
10 which said driving voltage is set to 0V being varied to perform a gradation display.

16. A liquid crystal shutter driving method according to claim 14, wherein

15 the voltage applied to said liquid crystal shutter in said scan term is varied from 0V to perform a gradation display.

17. A liquid crystal shutter driving method according to claim 14, wherein

20 a single driving term of said liquid crystal shutter is controlled, depending on the operating temperature, so as to be increased at a time of a low temperature but reduced at a time of a high temperature.

18. A method of driving a liquid crystal shutter according to claim 3,
25 wherein

1000
 900
 800
 700
 600
 500
 400
 300
 200
 100
 0